

GRAIN SPREADERS



BROCK MODEL GS-3 GRAIN SPREADER



Brock's Model GS-3 Grain Spreader distributes grain for optimum drying/aeration uniformity. This unit is rated at 3,000 bushels per hour, depending on moisture and type of grain.



Spreader impellers can be adjusted to match the grain throw to the bin's diameter. Spreader can be adjusted to fit bins from 24 to 48 feet (7.3 to 14.6 m) in diameter.

Spreader Features Include:

- ◆ A ½-horsepower totally-enclosed C-face motor mounted directly to an in-line gear reducer for no loss of horsepower and no belts to maintain or replace.
- ◆ Galvanized steel construction for durability and low maintenance.
- ◆ Wear plate (shown below) on motor end protects motor in grain flow.



Adjustable Hanging Brackets allow a wide range of hanging heights.

Optional Centering Cone and Flow Guides (shown on spreader above) are used in systems with a flow rate of less than 2,000 bushels per hour.



Brock Grain Systems - A Division of CTB, Inc.
Milford, IN - Kansas City, MO - Frankfort, IN
E-Mail: brock@brockmfg.com
Internet: www.brockmfg.com
Phone: 765-654-8517 - Fax: 765-654-8510
International inquiries call: 1-574-658-9323