

*GRAIN SPREADERS*



# BROCK MODEL GS-3 GRAIN SPREADER



**Brock's Model GS-3 Grain Spreader** distributes grain for optimum drying/aeration uniformity. This unit is rated at 3,000 bushels per hour, depending on moisture and type of grain.



**Spreader impellers** can be adjusted to match the grain throw to the bin's diameter. Spreader can be adjusted to fit bins from 24 to 48 feet (7.3 to 14.6 m) in diameter.

## Spreader Features Include:

- ◆ A ½-horsepower totally-enclosed C-face motor mounted directly to an in-line gear reducer for no loss of horsepower and no belts to maintain or replace.
- ◆ Galvanized steel construction for durability and low maintenance.
- ◆ Wear plate (shown below) on motor end protects motor in grain flow.



**Adjustable Hanging Brackets** allow a wide range of hanging heights.

**Optional Centering Cone and Flow Guides** (shown on spreader above) are used in systems with a flow rate of less than 2,000 bushels per hour.



**Brock Grain Systems** - A Division of CTB, Inc.  
Milford, IN - Kansas City, MO - Frankfort, IN  
E-Mail: [brock@brockmfg.com](mailto:brock@brockmfg.com)  
Internet: [www.brockmfg.com](http://www.brockmfg.com)  
Phone: 765-654-8517 - Fax: 765-654-8510  
International inquiries call: 1-574-658-9323